

LEDVANCE® Surface Circular

Indoor luminaires | LED surface mounted luminaire



Area of application

- Corridors
- Stairways
- Bathrooms
- Foyers


Product benefits

- Direct replacement for conventional 2x18W and 2x26W CFL luminaires
- Energy savings of up to 55% compared to conventional luminaires
- Easy and quick installation
- Versions with movement and daylight sensor available (microwave sensor)
- Very homogenous light
- LEDs cover protection for safe installation
- Available certificates: CE, CB, TUEV SUED

Product features

- Luminaire efficacy: up to 80 lm/W
- Luminous flux: up to 1920lm
- Available with color temperature: 3000K, 4000K
- Beam angle: 120°
- Type of protection: IP44
- Impact resistance: IK03
- Aluminum housing, PMMA cover
- Ambient temperature in operation: -20...+40 °C
- Lifetime (L70/B50): up to 30000h
- 3-years guarantee

Technical data



Product description	GTIN (EAN)	Nominal wattage [W]	Nominal voltage [V]	Power factor [λ]	Luminous flux [lm]	Luminaire efficacy [lm/W]	Colour temperature [K]	CRI index [Ra]
Surface-C LED 350 18W/3000K IP44	4058075000742	18W	230V	> 0.5	1440	80	3000K	>80
Surface-C LED 350 18W/4000K IP44	4058075000766	18W	230V	> 0.5	1440	80	4000K	>80
Surface-C LED 400 24W/3000K IP44	4058075000780	24W	230V	> 0.5	1920	80	3000K	>80
Surface-C LED 400 24W/4000K IP44	4058075000803	24W	230V	> 0.5	1920	80	4000K	>80
Surface-C LED 400 24W/3000K S IP44	4058075000827	24W	230V	> 0.5	1920	80	3000K	>80
Surface-C LED 400 24W/4000K S IP44	4058075000841	24W	230V	> 0.5	1920	80	4000K	>80

Product description	Beam angle	Rated life time L70 / B50 [h]	Type of protection IP rating	Protection class	Product size l x w or ø [mm]	Height h [mm]	Body colour
Surface-C LED 350 18W/3000K IP44	120°	30000	44	I	Ø350	115	white
Surface-C LED 350 18W/4000K IP44	120°	30000	44	I	Ø350	115	white
Surface-C LED 400 24W/3000K IP44	120°	30000	44	I	Ø400	120	white
Surface-C LED 400 24W/4000K IP44	120°	30000	44	I	Ø400	120	white
Surface-C LED 400 24W/3000K S IP44	120°	30000	44	I	Ø400	120	white
Surface-C LED 400 24W/4000K S IP44	120°	30000	44	I	Ø400	120	white

Packaging information

Product description	GTIN (EAN)	Dimensions EAN10 l x w x h [mm]	Gross weight EAN 10 [g]	Volume [dm³]	Packaging unit [Pieces/unit]
Surface-C LED 350 18W/3000K IP44	4058075000742	386 x 386 x 120	1172	20.10	5
Surface-C LED 350 18W/4000K IP44	4058075000766	386 x 386 x 120	1172	20.10	5
Surface-C LED 400 24W/3000K IP44	4058075000780	440 x 440 x 135	1351	28.99	5
Surface-C LED 400 24W/4000K IP44	4058075000803	440 x 440 x 135	1351	28.99	5
Surface-C LED 400 24W/3000K S IP44	4058075000827	440 x 440 x 135	1351	28.99	5
Surface-C LED 400 24W/4000K S IP44	4058075000841	440 x 440 x 135	1351	28.99	5

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.