

PRODUCT DATASHEET FLOODLIGHT LED 100 W 6500 K BK

LEDVANCE FLOODLIGHT LED | LED floodlight luminaires



AREAS OF APPLICATION

- Replacement for floodlights with halogen lamps
- Car parks and underpasses
- Garages
- Public areas
- Building facades
- Construction areas

PRODUCT BENEFITS

- Energy savings of up to 90 % compared to halogen lamp floodlights
- Optimized weight and size due to compact design
- Very homogenous light

PRODUCT FEATURES

- Luminaire efficacy: up to 100 lm/W
- Beam angle: 100°
- Type of protection: IP65



TECHNICAL DATA

Electrical data

erating mode Electronic control gear (EVG)	
Nominal wattage	100.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz


Photometrical data

Color temperature	6500 К
Luminous flux	10000 lm
Light color (designation)	Cool Daylight
Color rendering index Ra	≥80

Light technical data

Beam angle 100.00 °

Dimensions & weight



Length	253.0 mm
Width	243.0 mm
Height	92.5 mm

Colors & materials

Body material	Aluminum
Product color	Black
Cover material	Glass

Temperatures & operating conditions

Lifespan

	Lifespan	30000 h
--	----------	---------

Capabilities

Dimmable	No
Type of connection	Cable, 3-pole
LED module replaceable	Not replaceable

Certificates & standards

Protection class	1
Type of protection	IP65
Standards	CE/CB/TÜV SÜD/EAC/ROHS
Protection class IK (shock resistance)	IK08

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075811010	FLOODLIGHT LED 100 W 6500 K BK	Shipping carton box 1	328 mm x 295 mm x 162 mm	15.68 dm³	4192.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.